



Self/2000, Self/4000, Self/5000

The latest generation of unattended terminals

The compact all-in-one terminals are the ideal space-saving solution for kiosks, vending machines and other indoor and outdoor applications.

The Self terminals combine NFC, chip card and magnetic stripe readers in a single, high-performance device. Whether touch display or physical keyboard - they are all characterized by an elegant, modern design and a appealing user interface. The terminals support all major credit and debit cards as well as all leading apps for mobile payments. They are the reliable solution at your unattended point of sale.

ALL ADVANTAGES AT A GLANCE:

- The Tetra-based platform guarantees high performance
- Compact and attractive
- Installation format complies with EVA standard
- Security standard PCI PTS 5.x
- ep2-certified
- Vandal-proof/water and dust-proof tested according to IK & IP



CONTACTLESS



MOBILE
PAYMENTS



MAXIMUM
SECURITY



TOUCH
DISPLAY

Technical details

	SELF/2000	SELF/4000	SELF/5000
			
Processor	Cortex A5	Cortex A5	Cortex A5
Memory	512 MB RAM, 512 MB Flash	512 MB RAM, 512 MB Flash	512 MB RAM, 512 MB Flash
Display	Capacitive touch display 240 × 320 pixels	Physical pinpad 640 × 240 pixels	Capacitive touch display 240 × 320 pixels
Keyboard	Yes - integrated in the touch display	Yes - physical pinpad	Yes - integrated in the touch display
Card reader	Contactless	Contactless Chip card reader Magnetic stripe card reader	Contactless Chip card reader Magnetic stripe card reader
Communication	LAN 4G (optional)	LAN 4G (optional)	LAN 4G (optional)
Power supply	9 - 16 V DC 10 - 45 V DC (via MDB add-on box)	9 - 16 V DC 10 - 45 V DC (via MDB add-on box)	9 - 16 V DC 10 - 45 V DC (via MDB add-on box)
Dimensions W × H × D mm	85 × 107 × 99,2	85 × 107,2 × 109,6	85 × 107,2 × 109,6
Required section	EVA compliant	EVA compliant	EVA compliant
Weight	340 g	392 g	443 g
PCI version	PCI PTS 5.x	PCI PTS 5.x	PCI PTS 5.x
Ambient conditions	-20 °C to +70 °C IP Ingress Protection (degree of protection) IP65 Shock Protection (impact protection) IK09	-20 °C to +70 °C IP Ingress Protection (degree of protection) IP44 Shock Protection (impact protection) IK09	-20 °C to +70 °C IP Ingress Protection (degree of protection) IP44 Shock Protection (impact protection) IK09
Cash register connection	TIM via LAN MDB 4.2	TIM via LAN MDB 4.2	TIM via LAN MDB 4.2
Options	4G (2G) add-on box MDB add-on box	4G (2G) add-on box MDB add-on box	4G (2G) add-on box MDB add-on box

You can find your local contact at: worldline.com/merchant-services/contacts

